

The AMR600 series readers are QR code as well as RFID card readers in a single package with various mounting options.

The AMR620 are high performance readers providing high speed and accurate recognition capability with both desktop and well as flush mount options. It can recognize QR/1D/2D barcodes and read up to 64 bit ISO14443A/B with output to Wiegand port.

The AMR612C is a low cost recessed mount QR/1D/2D and MIFARE reader with Wiegand output up to 34 bits.

Ideal for many applications including Visitor Management, Facilities Booking, Staff Access, etc.



AMR620C



AMR622M



AMR612C

Key Features



- High scanning speed and recognition rate



- Supports multiple sizes of QR, 1D and 2D codes



- Wiegand/RS232/RS485/USB interface



- Built-in with RFID contactless card reader ISO14443 A/B & QR code

Technical Specifications

Specifications*	AMR612C	AMR620C	AMR622M
Description	AMR600 Recess Mount Mifare & QR Reader	AMR600 Recess Mount QR Reader	AMR600 Surface Mount RFID & QR Reader
Decoding Support	QR, 1D, 2D		
Communication	Wiegand 34-bit	Wiegand 34/64/66-bit	
LED Indicator	Green, Red	Blue, Red	
Buzzer	Yes		
Contactless	MIFARE 32-bit	ISO14443 A/B, FeliCa	
Input Voltage	8 ~ 12VDC	9 ~ 24VDC	
Dimensions (HxWxD)	86mm x 86mm x 42mm	71mm x 76mm x 47mm	95mm x 91mm x 90mm
Weight	150g	170g	
Operating Conditions	-20°C~70°C, Humidity 10%~90%	0°C~50°C, Humidity 30%~90%	

*Specifications are subject to change without prior notice

Ordering Information

Model No.	Description
AMR612C	AMR600 Recess Mount Mifare & QR Reader
AMR620C	AMR600 Recess Mount QR Reader
AMR622M	AMR600 Surface Mount RFID & QR Reader